

Lifting, Rigging and Safety Equipment Specialist

Montreal
Quebec
Saguenay
Moncton



LAM-É
ST-PIERRE

Lifting Solutions Group
Axel Johnson International



LXC Sling



Montreal
514 354-4219

Quebec
418 652-9759

Saguenay
418 696-9759

Moncton
888 830-5438



MADE IN QUEBEC

Lifting, Rigging and Safety Equipment
Montreal | Quebec | Saguenay | Moncton

Montreal
514 354-4219

Quebec
418 652-9759

Saguenay
418 696-9759

Moncton
888 830-5438



High-Strength LXC Round Synthetic Slings

The **LXC** sling is designed for both specialized and repetitive lifting. It is ideal for handling delicate equipment, moving heavy parts, or avoiding damage to the finish of equipment being lifted.

The **LXC** sling has a safety factor that meets or exceeds industry standards. The LXC sling enables simple and safe lifting.

The **LXC** sling gives you a better grip on the load and allows you to perform more lifting operations in the same amount of time compared with a conventional sling.

The **LXC** sling is made with HMPE FIBER, which is high-performance and renowned for its very high strength compared with steel and polyester.

The **LXC** sling has a double jacket that protects the load-bearing yarns, extending the sling's service life. The contrasting color of the second jacket makes inspection easier and indicates the sling's condition before use.

The **LXC** sling is made from premium-quality material. Its nylon outer jacket includes a protective microfilm. This protection prevents oils, mold, and grease from penetrating the LXC sling.

October 2026

1 HMPE fiber.

2 Have a 5:1 or 7:1 safety factor.

3 Include water-repellent protection.

4 Meet or exceed ASME B38.9, CSHA and W51DA standards.


5 Available in various lengths and capacities.

6 Come with a certificate of conformity.

7 Have a double jacket.




Lifting examples:




Example 1: Vertical lift using a 1-1/4" x 10' chain sling

- a. Capacity: 72,300 lb
- b. Chain sling weight: **249lb**



Example 2: Vertical lift using a 2" x 10' wire rope sling

- a. Capacity: 74,000 lb
- b. Wire rope sling weight: **175lb**



Example 3: Vertical lift using a 6" x 10' LXC sling

- a. Capacity: 85,000 lb
- b. LXC sling weight: **40lb**

AVAILABLE ACCESSORIES:

Custom-made protective components

Protective pad

Removable protector