



WEZ

Grab for Angular Concrete Products WEZ

Specially developed for handling L-stones and similar products.

The lifting eye can be adjusted to the center of gravity of all prevalent products being lifted to let it hang vertically.

Standard Specifications:

- ▶ Lifting eye for attaching to crane hook.
- ▶ Highly durable and exchangeable rubber grippers.
- ▶ Automatic release for the fully automatic change over from "full" to "empty".
- ▶ Leaves no black marks.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
WEZ-2 ①	50 – 250 (2" – 9¾")	2,000 (4,400)	55 (120)	5310.0347
WEZ-6 ①	50 – 300 (2" – 11¾")	6,000 (13,200)	160 (350)	5310.0375



FVZ-UNI

Mechanical Boulder Grab FVZ-UNI

Suitable for handling boulders.

Stones of almost all shapes can be lifted and laid to the exact millimetre.

▶ With chains (by changing the chain-position,

the clamp can be lifted after setting of the stone).

▶ Automatically adjustable gripping range from 0 to a maximum of 950 mm.

▶ With lifting eye for attaching to crane hook.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FVZ-UNI	0 – 950 (0 – 37½")	1,500 (3,300)	99 (218)	5310.0272



H-FVZ-UNI

Manual Boulder Grab H-FVZ-UNI

A manual boulder grab for smaller boulders which can be carried by two men.

▶ Additionally equipped with a ring-eyelet to be hooked onto any kind of lifting device,

regarding the admissible working load limit.

▶ Equipped with a simple and fast gripping range adjustment.

▶ Galvanised finish

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
H-FVZ-UNI ①	0 – 600 (0 – 23½")	200 (440)	18 (40)	5320.0086



FZ

Flat Grab FZ

FZ for transport of slabs.

▶ Narrow grippers turn standing slabs or erect laying slabs.

▶ No problem to grip even tight standing slabs.

▶ No damage to the surface of the slabs due to gentle handling with rubber grippers.

▶ High security by enormous transmission of 5:1.

▶ A spring tension prevents from unintentional slipping off the clamp.

▶ Lifting band instead of chain or rope: low dead weight, no squeezing, no hurts.

▶ Suitable for nearly all kinds of material.

Type	Gripping Range* W mm (in)	Working Load Limit WLL kg (lbs)	Dead Weight kg (lbs)	Order-Number
FZ	0 – 60 (0 – 2½")	800 (1,760)	6 (13)	5310.0278

*Gripping range indicates the minimum and maximum pack measurements of building materials, which can be picked-up with this grab.

① Durable surface protection by galvanizing